



Product Code: ALU-PET-ALU

Description: Polyester film laminated with aluminum on both sides

Composition: Aluminum foil
Polyester film

TECHNICAL PROPERTIES:

Structure	Thickness	Weight gr/m ²	Yield m ² /kg	Tensile Strength N/mm ² (a)	Elongation At Break % (a)	Breaking Strength N / 15 mm (a)	Peel Strength N / 15 mm (b)
Alu9 PET12 Alu9	35 m	70	14	≥ 70	≥ 40	≥ 36	≥ 2
Alu20 PET12 Alu20	57 m	130	8	≥ 75	≥ 12	≥ 64	≥ 2
Alu25 PET12 Alu25	67 m	157	6	≥ 75	≥ 14	≥ 75	≥ 2
Alu9 PET15 Alu9	38 m	75	13	≥ 75	≥ 45	≥ 42	≥ 2
Alu9 PET19 Alu9	42 m	80	12	≥ 75	≥ 50	≥ 47	≥ 2
Alu9 PET23 Alu9	46 m	86	12	≥ 100	≥ 60	≥ 60	≥ 2
Alu12 PET15 Alu12	44 m	91	11	≥ 75	≥ 15	≥ 50	≥ 2

(a) ASTM D 882-95T (b) ASTM D 1876-93