

# H62310 | TRUST commercial Satin 245

MICROPOROUS RESIN-COATED PAPER

## PRODUCT SPECIFICATION \*

<b>Weight</b> DIN EN ISO 536	g/m <sup>2</sup>	248	± 6
<b>Thickness</b> DIN EN ISO 534	µm	242	± 6
	mil	9,5	± 0,2
<b>Gloss BYK (60°)</b> ISO 2813		19	± 5
<b>Colour Elrepho UVO (D65)</b> ISO 2469	L	94,2	± 0,5
	a	-0,2	± 0,3
	b	-2,6	± 0,5
	delta b	<0,7	
<b>il Pro2</b>	L*M0	95,3	
	a*M0	-0,3	
	b*M0	-2,7	
	L*M1	95,3	
	a*M1	-0,3	
	b*M1	-3,0	
<b>CIE whiteness (D65/10°) min.</b> ISO 2469		> 94	
<b>Opacity min.</b> ISO 2469	%	> 94	

### Printability

Simplex printable

### Printing Technology

💧 Inkjet water-based

### Compatibility

Compatible with all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

### Available on request



### Certificates



Fogra 25488-3

## KEY APPLICATIONS

### Proof & Prepress

- Proofs for offset, gravure and screen printing
- Mock-ups
- Dot-proofs
- Contract, design and check proofs

## BENEFITS & PROPERTIES

- Reproducibility by outstanding media colour consistency
- Large colour gamut
- Pin-sharp details
- Instant dry
- Universal compatibility for printers and inks

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 01/2016