

J43340 | E-CANVAS Matt 340

COATED FABRIC

PRODUCT SPECIFICATION *

Weight	g/m ²	344	± 20
Thickness	µm	380	± 25
	mil	15.0	± 1.0
Gloss BYK (20°)		2	± 0
Gloss BYK (60°)		5	± 0
Gloss BYK (85°)		10	± 0
Colour Elrepho UVO (D65)	L	94,6	± 1,0
	a	0,0	± 0,3
	b	1,1	± 0,8
	delta b	1,7	± 1,2
CIE whiteness (D65/10°)		> 82	
Opacity	%	> 96	

Printability

Simplex printable

Printing Technology

- Indigo printing systems
- Dry toner systems

Compatibility

HP Indigo with One-Shot technology.
Authorised for Xeikon 8000 series.

KEY APPLICATIONS

Wall Decoration

- Canvas on stretcher frames
- Photos
- Art reproduction

BENEFITS & PROPERTIES

- Specially designed E-CANVAS coating
- Deep blacks
- Vivid colours
- Printable with full HP Indigo production speed
- First real polycotton Canvas material with well-known HP Indigo print performance
- Instant dry
- Perfect stretching and framing performance
- High light fastness with HP Indigo ElectroInk
- Acid free
- Authorised for Xeikon 8000 series (more information: <https://printmedia.xeikon.com>)

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 02/2016