

PREMIUM LIGHT BOX FABRIC

PRODUCT: ST-129

FEATURES / APPLICATIONS:

- 100% polyester knit fabric, matte finish
- Stop light leak, uniform light transmittance, presents perfect graphic texture.
- Lighter weight, softer, more textile texture
- Been coated for dye-sub direct printing, also suitable for dye-sub transfer

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	260g/sq.m	7.6 oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060	55x55 dtex	50x50 denier
Weave Method	N/A	Warp-knitted 2 bar	
White Point	CIE/D65	≥123	
Shrinkage	N/A	≤2% (190°C , 1min)	
Flame Resistance	DIN 4102	NFPA 701, B1	
Recommend fixation temperature	N/A	190°C-210°C , 1-2min	
Transfer temperature	N/A	190°C-210°C , 1-2min	
Yellowing temperature	SUPRKC REX-C400	240°C	
Width	N/A	Max 320cm	126"
Standard Length	N/A	50m	55yd

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
Screen Printing	Dye Transfer	Dye Direct	
	<input type="checkbox"/>	<input type="checkbox"/>	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd

(Soyang Headquarters)

West 19th FL, Yongtong
Information plaza, No. 141
Huancheng Bei Road, Hangzhou

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China.

Soyang Hangzhou Factory

No.1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR,
China

Soyang Europe Ltd

Calder House Metcalf
Drive
Altham Industrial estate

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982