

Soft-PVC 180μ, white glossy
Kraft paper, ultra removable

K1144W
Technical Product Information

Grade characteristics

Description	Soft-PVC white glossy
Application	Decorative labels for cosmetics, food.
Coating	With certified Indigo-topcoat
Approvals	Complies with EU-Regulations: Packaging 94/62/EC ; Heavy Metal, PBB and PBDE
Remarks	2003/11; Suitable for HP Indigo I

Description

Physical properties	Value	Unit	Test method
Caliper	180	μm	ISO 534
Stretch at break md	> 160	%	DIN 53455
Tear resistance md	> 26	Mpa	ISO 1924/1

Adhesives

Ultra-removable glue M1: residue free, transparent acrylic ultra removable adhesive

Physical properties

Physical properties	Value	Unit	Test method
Adhesion* M1 Ultra-removable	< 2	N/25mm	FTM 1

Description

Liner H18:

135g/m², chlorine free bleached

Kraftliner

Physical properties	Value	Unit	Test method
Substance	135	g/m ²	ISO 536
Caliper	136	μm	ISO 534

Storage and application data

Recommended processing temperature

Product application temperature

Life expectancy

Shelf life at 23°C / 50% r.h.

min. + 5°C - 30°

up to + 90°C

1 year

1 year in original packing *