**TECHNICAL DATA SHEET** 

## **DESCRIPTION OF THE PRODUCT** Product name : WOAF GLOSS 220 g/m<sup>2</sup> UNITS CHARACTERISTICS METHODS MIN TARGET MAX Basis weight g/m² ISO 536 210,0 220,0 230,0 -ISO 534 190,0 200,0 210,0 Caliper μm ISO DP 5629 Machine Direction 4,0 4,6 -Stiffness Kodak mNm Cross Direction 2,3 2,8 ISO 1974 Machine Direction 750 850 \_ Tear strength Elmendorf mΝ Cross Direction 850 950 ISO 1924 Machine Direction 9,5 11,0 Tensile strength kN/m Cross Direction 4,8 5,6 \_ Brightness R-457 % D65 Top side 89,0 91,0 93,0 Opacity % D65 Top side 98,0 98,7 Yellow Index % D65 Top side -8,3 -6,3 -4,3 Gloss 60° % 45,0 49,0

## **OTHER CONDITIONS**

## STORAGE AND USE

\* If the temperature and moisture conditions of the storage are too different from the printing room conditions, packed paper needs to be transfered in the printing room few days before printing.

- \* Reels need to be kept packed until the beginning of the printing.
- \* If one reel is not used in totality, the remaining reel needs to be repacked immediately.