



2000M Anti-Slip White Matte Floor Graphic Film is a thick, white calendered film suitable for floor applications. It comes with a directly printable anti-slip surface that doesn't need any overlamine and a removable adhesive for fast and clean removability.

## Features

1. Directly printable anti-slip surface without impacting anti-slip properties
2. No need for protective lamination
3. Anti-slip certification
4. Fire certification
5. Removable adhesive, no need to clean after the film removal

## Application

Ideal for short term indoor floor graphic promotions,  
Suitable for surface flooring, ceramic tile, wood composites, etc.

Item NO.: 2000M

Description Anti-Slip White Matte Floor Graphic Film

## Performance and Parameters

Property	Typical Value	Standard
PVC Film	Monomeric Film 200 μm / 6.6mil	GB/T 451.3-2002
Glue	Clear Removable Adhesive	---
Liner	140gsm /SSPE	GB/T 451.2-2002
Air Release / Non-Air Release	Non-Air Release	---
Opacity [%]	>98%	GB/T 9754-2007
Peel Strength [lbf/in] 15min [lbf/in]	1.5-2.5	FTM1-FINAT
Peel Strength [lbf/in] 24hrs [lbf/in]	2.5-3.5	FTM1-FINAT
Gloss [60°]	3 - 5	GB/T 9754-2007
Dimensional Stability	<0.5mm	---
Anti-Slip Resistance	R10	DIN 51130
Shelf time	1 year,unopend in original packaging	---
Durability	6 Months (Printed)	---
Flame Resistance	B1	

## Size

Width	50"/ 54"
Length	50m

## Ink Compatibilities

Eco-solvent	UV
√	√

## Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources.  
 Recommended storage temperature and humidity: 15 ° C (59 ° F) ~ 35 ° C (95 ° F), 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

### Disclaimer:

All the declarations and technical information of the products are obtained through reliable testing under high-precision equipment; however, their integrity or reliability cannot be guaranteed, and Jiacheng does not guarantee this. Our sole responsibility is that Replace all quantities of the product if it proves to be defective. Jiacheng is not liable for direct or indirect damages caused by the use or inability to use the product. Before use, the user should determine if the product is suitable for its use. Unless otherwise agreed with Jiacheng, any statements or recommendations other than those contained in the published technical information are not valid.