

Item No. DB201S-3A2

Description 300D Self Adhesive Wall Covering Fabric

Performance and Parameters

Property	Typical Value	Standard
Material	100% Polyester	DIN 60001,ASTM D7641
Substrate	220±10gsm	GB/T 451.3-2002
Yarn	300D*300D	DIN EN ISO 2060,ASTM D1907
Weave Method	Woven	---
Total Weight	390gsm	ISO536
Glue	Water Base Removable Light Grey Adhesive	---
Liner	120gsm /SSPE	GB/T 451.2-2002
Thickness	385±30µm	ISO534
Opacity	>85%	ISO2471
Whiteness	120±10	ISO11475
Color	L*: 92.0±2.0; a*: 4.5±2.0; b*: -10.0±2.0	GB/T 7974-2002
Peel Strength 15min [lbf/in]	1.0-1.5	FTM1-FINAT
Peel Strength 24hrs [lbf/in]	1.5-2.5	FTM1-FINAT
Gloss [60°]	3-5	GB/T 9754-2007
Shelf time	1 year,unopened in original packaging	---
Application	Mural,Wall Covering,Exhibition,Display Systems	---

Size

Width	0.914 m/1.07 m/1.27 m/1.524 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	30 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Compatible Inks

Solvent	Eco-Solvent	UV
√	√	√

Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Disclaimer:

The technical parameters of these products were tested in the laboratory environment, this is only serve as a reference. Before use, the user should determine the suitability of the product. Statements or recommendations contained in the technical information are not valid until the agreement is signed.