

Super Tenacity Backlit Banner

Soyang Code: BW4-560(1018)

FEATURES / APPLICATIONS:

- Super strong tenacity for high end back-lit display
- White translucent substrate for large format back-lit display
- Matte & gloss surface available

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	560g/m ²	/
Base Fabric	DIN 60001	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier
Tensile Strength	DIN EN ISO 1421	1800x1460 N/5cm	202x164 lbs/inch
Tear Strength	DIN 53363	335x290N	75x65lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102	Can achieve NFPA-701/B1 FR based on order	
Width	N/A	Max 500cm	197 Inch

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Europe Ltd

38 Peel Industrial Estate, Bury, Manchester BL9 0LU UK.

www.soyang.co.uk

P. 0044-870 112 7445

F. 0044-870 112 7446

Soyang Europe B.V. (Europe Warehouse)

Van der Helm - Hudig Moerdijk B.V. Orionweg 6-8, 4782 SC Moerdijk The Netherlands

www.soyang.co.uk

P. 0044-870 112 7445

F. 0044-870 112 7446