





STARLIGHT BACKLIT FABRIC

PRODUCT: ST-601

FEATURES:

- 100% Polyester that has different coating on two sides, which allows you to print solvent and UV on one side or dye-sublimation on the other.
- Combined with UV resistant or dispersed inks.



APPLICATIONS:

- Led light boxes Frame systems Pop-up tens Sun-umbrellas

PROPERTIES	TEST METHOD	METRIC	IMPERIAL	
Total Weight	DIN EN ISO 2286-2	175g/sq.m	5 oz/sq.yd.	
Base Fabric	DIN 60001	Polyester	Polyester	
Weave Method	N/A	Woven		
White Point (CIE/D65)	CIE86/ASTME313-00(D65/10,SCI)	≥109		
Shrinkage	N/A	≤2% (190°C , 1min)		
Flame Resistance	1	DIN 4102-1-B1,NFPA 701		
Recommend fixation temperature	N/A	190°C-210°C,1-2min		
Transfer temperature	N/A	190℃-210℃,1-2min		
Yellowing temperature	SUPRKC REX-C400	170°C(sticky)		
Width	N/A	Max 320cm	126"	
Standard Length	N/A	50m	55yd	

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
	0		
Screen Printing	Dye Transfer	Dye Direct	
	0		

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang	Techno	logies	Co.,	Ltd
(Sovang	Headq	uarter	s)	

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690 F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf
Drive
Altham Industrial estate

www.soyang.co.uk

P. 0044 (0) 161 765 3400 F. 0044 (0) 1282 772982