

Grade characteristics

Description	PET silver matt
Application	Decorative labels for cosmetics, food
Coating	With Indigo Topcoat
Approvals	Complies with EU-Regulations: Packaging 94/62/EC ; Heavy Metal, PBB and PBDE
F i m	2003/11;
Remarks	Suitable for Indigo Printing I

Description

Physical properties	Value	Unit	Test method
Caliper	50	µm	ISO 534
Stretch at break md	--	%	DIN 53455
Tear resistance md	--	N/mm ²	ISO 1924/1

A
d Permanent glue P3:
h permanent glue P3, comply with EN 71/3 (application on toys Copolymeres Acrylat), and European packaging **e** directive 94/62/EC (heavy metals).
s

Physical properties	Value	Unit	Test method
Adhesion* P3 →permanent	14 ±3	N/25mm	Finat 1 24h on glass

i
v
e

Description

D18
 siliconised Kraftliner, double-sided PE-coated

L
i
n
e
r

Physical properties	Value	Unit	Test method
Substance	140	g/m ²	ISO 536
Caliper	150	µm	ISO 534

Storage and application data

Recommended processing temperature	min. + 5°C - 30°
Product application temperature	up to + 90°C
Life expectancy	1 year
Shelf life at 23°C / 50% r.h.	1 year in original packing *