





TECHNICAL DATA SHEET DDIC050

Product description:

- Clear PET Gloss Self Adhesive 50my
- Applications: Label for advertising products, signage, decoration
- Outdoor and indoor use*
- Adhesive high bond strength to polar and non-polar surfaces
- Optimized for HP-Indigo printing machines
- Excellent ink adhesion
- Excellent machine runnability

| Parameter | Value |
|---------------------------|--|
| Dimension (mm) | 480 X 330 |
| | 750 X 530 |
| Face Stock Thickness (μm) | 50 ± 6 |
| Adhesive | Initial tack 10N/25mm (FTM9 glass) |
| | Peel at 180 ⁰ 11N/25mm (FTM1) |
| Liner Thickness (µm) | 200 ± 16 |
| Surface | Clear, Gloss |

Processing Recommendations:

- Substrates should be acclimatized at room temperature 24 h before printing.
- Print at room temperature with relative humidity between 50-60%.

Storage Conditions:

- Storage should be at temperatures of 10-30°C and relative humidity of 50-60%. Do not expose to direct Sun light.
- Keeping the recommended storage conditions in original packaging will increase product shelf life up to 1 year.

*Users should perform their own tests in order to verify the suitability for a specific application Alon Tavor Ind. Zone, Israel

www.jolybar.com jolybar@jolybar.com +972-4-6407333