

# TECHNICAL DATA SHEET

## DVIM300

### Product description:

- PVC white matt 2 sided coated 300  $\mu\text{m}$
- Applications: Signage, tags, business cards, placements
- 2 sided optimized for HP-Indigo printing machines
- Excellent ink adhesion
- Excellent machine runnability

Parameter	Value
Dimension (mm)	480X330 720X520
Thickness ( $\mu\text{m}$ )	300 $\pm$ 21
Tensile Strength (N/mm <sup>2</sup> )	>42
Vicat softening point (ASTM 1525)	74 $\pm$ 2
MD Dimensional stability (DIN 53377 140°C / 10min) %	8
Surface	Satin / Satin

### Processing Recommendations:

- Substrates should be climatized at room temperature 24 h before printing.
- Print at room temperature with relative humidity between 50-60%.

### Storage Conditions:

- Storage should be at temperatures of 10-30°C and relative humidity of 50-60%. Do not expose to direct Sun light.
- Keeping the recommended storage conditions in original packaging will increase product shelf life up to 6 months.

Users should perform their own tests in order to verify the suitability for a specific application

Alon Tavor Ind. Zone, Israel

[www.jolybar.com](http://www.jolybar.com)

[jolybar@jolybar.com](mailto:jolybar@jolybar.com)

+972-4-6407333

7.19