

BOPP (PP) White, P22, Sheets

Facestock:

A White Bi-Oriented Cavitated Polypropylene. Either Corona treated, clay coated, top coated for conventional printing methods or top coated for HP Indigo printing.

Laminate Data:

Facestock		Liner		Total (±10%)	
Type	Caliper (μ)	Type	gsm	Caliper (μ)	Weight (gsm)
Polypropylene White	58	CCK	135	210	194
White Matt	54	CCK		206	194

Adhesive- P22:

Description:

General purpose high performance permanent acrylic adhesive

Performance & Use:

This adhesive has been designed to adhere to a variety of substrates, especially carton-board and low energy surfaces such as polyethylene.

Initial tack is high and a strong bond is ultimately formed.

Initial Tack

Peel Adhesion 180o

9 N/25mm	FTM9 glass
10 N/25mm	FTM1 St.St

Temperature:

Min' application: >0oC

Service: -20 oC/100 oC

Printing methods:

Suitable for various printing methods, including: Laser printing, Thermal transfer, Letterpress, Offset, Flexo, and silk screen printing.

Shelf life:

2 Years under storage conditions as defined by FINAT.

Temperature: 20-25oC

Humidity: 40-50%RH

All figures to be considered as typical values

This data is intended to be a guide to the values which may generally be expected, since the final use of the product is outside our control, we strongly advise prior testing of its suitability for a particular purpose.