

TECHNICAL DATA SHEET

DDIC080

Product description:

Clear Gloss PVC Self Adhesive 80my

Applications: Label for advertising products, signage, decoration

Optimized for HP-Indigo printing machines

Excellent ink adhesion

Excellent machine runnability

Parameter		Value	460
Dimension (mm)		X 320 480 X	
		330 750 X	
		530	80±8
Face stock	Thickness (µm)	>150	>25
	Stretch at Break md (%)	≥70	13±2
	Tear Resistance md (mPa)	17±3	160±5
	Gloss 60o (ASTM D523)	Clear Gloss	
Adhesive	Initial Peel Strength (N/25mm), FTM 1		
	Final Peel Strength (N/25mm), FTM 1		
Liner	Thickness (µm)		
Surface			

Processing Recommendations:

Substrates should be acclimatized at room temperature 24 h before printing.

Print at room temperature with relative humidity between 50-60%.

Storage Conditions:

- Storage should be at temperatures of 10-30oC and relative humidity of 50-60%. Do not expose to direct Sun light.
- Keeping the recommended storage conditions in original packaging will increase product shelf life up to 1 year.

Users should perform their own tests in order to verify the suitability for a specific application

Alon Tavor Ind. Zone, Israel

www.jolybar.com

jolybar@jolybar.com

+972-4-6407333

1.20