

TECHNICAL DATA SHEET DDIG080

Product description:

White Gloss PVC Self Adhesive 80my

Applications: Label for advertising products, signage, decoration

Optimized for HP-Indigo printing machines

Excellent ink adhesion

Excellent machine runnability

Parameter		Value 460
Dimension (mm)		X 320 480 X 330 750 X 530
Face stock	Thickness (µm)	80±8
	Stretch at Break md (%)	>150
	Tear Resistance md (mPa)	>25
Adhesive	Permanent Clear High-Tack Adhesive	
	Initial Peel Strength (N/25mm), FTM 1	17±3 20±3
	Final Peel Strength (N/25mm), FTM 1	>90% 160±6
Face stock + adhesive	Opacity (%)	White Gloss
Liner	Thickness (µm)	
Surface		

Processing Recommendations:

Substrates should be acclimatized at room temperature 24 h before printing.

Print at room temperature with relative humidity between 50-60%.

Storage Conditions:

- Storage should be at temperatures of 15-35°C and relative humidity of 30-60%. Do not expose to direct Sun light.
- Keeping the recommended storage conditions in original packaging will increase product shelf life up to 1 year.

Users should perform their own tests in order to verify the suitability for a specific application

Alon Tavor Ind. Zone, Israel

www.jolybar.com

jolybar@jolybar.com

+972-4-6407333

1.20