

# PET glos silver Self-adhesive

## Technical product information

Product: 1154  
 Description: Polyester film silver shiny with print varnish  
 Application: Indigo Process  
 Compliance with EU Directive: Packaging Directive 94/62/EC; heavy metals, PBB and PBDE 2003/11

### Upper:

Thickness: DIN 53 353 50µm  
 Tear strength: DIN 53 353 lengthwise: k.A. N/mm<sup>2</sup> diagonal: k.A. N/mm<sup>2</sup>  
 Elongation at break: DIN 53 353 lengthwise:k.A.% diagonal: k.A. %

### Adhesives:

Copolymere acrylate, solvent free, excellent resistant to light and ageing, complies with the toy safety standards EN 71/ Part 3. All adhesives are suitable for use on dry and moist not fatty food (ISEGA declaration of no objection).

Adhesion strength FTM 1 Glass 24h in N/25 mm

Other product combinations are provided on request.

BEZ.	P3	P6
d16	>8	>8
k7w		>8

P3 = semi-permanent, P6 = permanent

### Cover: H + S

Chlorinefreebleached kraft paper, solvent free siliconization, climate stabilized for outstanding flatness

Cover: K w=white g=yellow d=high density

Super coated glassine paper, high tear strength, excellent cutting characteristics and solvent free for high dispensing speed

Cover: D

Kraft paper which has been laminated on both sides with polyethylene

Cover: C

Cover	Thickness EN 20 534	Grammage ISO 536
d16	0,165 mm 0,063 mm	144 g/m <sup>2</sup>
k7w		72 g/m <sup>2</sup>

**Application technical data:**

Recommended processing temperature: at least + 5 °C  
Temperature resistance: - 30 to + 90 °C  
Durability with appropriate application: 1 year  
Suitability for storage at 20°C, 50% r.F.: unopened original packaging 1 year

Alon Tavor Ind. Zone, Israel

[www.jolybar.com](http://www.jolybar.com)

[jolybar@jolybar.com](mailto:jolybar@jolybar.com)

+972-4-6407333

1.20