

## PET matt silver Self-adhesive

### Grade characteristics

<b>Description</b>	PET silver matt
<b>Application</b>	Decorative labels for cosmetics, food
<b>Coating</b>	With Indigo Topcoat
<b>Approvals</b>	Complies with EU-Regulations: Packaging 94/62/EC ; Heavy Metal, PBB and PBDE
<b>F</b>	2003/11;
<b>i</b>	
<b>m</b>	
<b>Remarks</b>	Suitable for Indigo Printing I

### Description

Physical properties	Value	Unit	Test method
Caliper	50	µm	ISO 534
Stretch at break md	--	%	DIN 53455
Tear resistance md	--	N/mm <sup>2</sup>	ISO 1924/1

**A**

**d** Permanent glue P3:

**h** permanent glue P3, comply with EN 71/3 (application on toys Copolymeres Acrylat), and European packaging e directive 94/62/EC (heavy metals).

**s**

Physical properties	Value	Unit	Test method
Adhesion*P3→permanent	14±3	N/25mm	Finat 1 24h on glass

**i**

**v**

**e**

### Description

D18

**L**

siliconised Kraftliner, double-sided PE-coated

**i**

**n**

**e**

**r**

Physical properties	Value	Unit	Test method
Substance			ISO 536
Caliper	140	g/m <sup>2</sup>	ISO 534
	150	µm	

### Storage and application data

#### Recommended processing temperature

Product application temperature	min. + 5°C - 30°
Life expectancy	up to + 90°C
Shelf life at 23°C / 50% r.h.	1 year 1 year in original packing *

Alon Tavor Ind. Zone, Israel

[www.jolybar.com](http://www.jolybar.com)

[jolybar@jolybar.com](mailto:jolybar@jolybar.com)

+972-4-6407333

1.20