

## TECHNICAL DATA SHEET

### DPIM080

Whiteopaque high grade polyester based synthetic print media with a matt finish.

Water and tear resistant, DPIM085 is extremely suitable for quick 'print and turn' jobs.

The growing range of applications includes indoor and outdoor POS signage, menu cards, tab sheets, labels and tags, just to name a few.

Property	Test method	Unit	DPIM200
Thickness Average	ASTM D-6988	µm	80 + 10
Weight		g/m <sup>2</sup>	230
Shrinkage	Internal test at 95°C/203°F	%	0,2
Brittleness	Internal test	°C (°F)	-40 (-40)
Initial tear strength	ASTM D1004	N	80
Stiffness	ISO 2493	mN	25
BEKK smoothness	ISO 5627	Sec	500-1000
Opacity	ISO 2471	%	96
Brightness	ISO 2470C		95
Whiteness Cie	ISO 11475		100
Gloss 85°	ISO 2813		10-15
Mass Density	ISO 534	g/cm <sup>3</sup>	1,16 ± 0,05
Shelf Life	20-25°C / 40-60%RH	At least 24 months	
Fire Class		Information upon request	

Alon Tavor Ind. Zone, Israel

[www.jolybar.com](http://www.jolybar.com)

[jolybar@jolybar.com](mailto:jolybar@jolybar.com)

+972-4-6407333