

## TECHNICAL DATA SHEET

### DPIM200

Whiteopaque high grade polyester based synthetic print media with a matt finish.

Waterand tear resistant, DPIM085 is extremely suitable for quick 'print and turn' jobs.

Thegrowing range of applications includes indoor and outdoor POS signage, menu cards,tab sheets, labels and tags, just to name a few.

Property	Test method	Unit	DPIM200
Thickness Average	ASTM D-6988	µm	200 + 10
Weight		g/m <sup>2</sup>	230
Shrinkage	Internal test at 95°C/203°F	%	0,2
Brittleness	Internal test	°C (°F)	-40 (-40)
Initial tear strength	ASTM D1004	N mN	80 25
Stiffness	ISO 2493	Sec	500-1000
BEKK smoothness	ISO 5627	%	96
Opacity	ISO 2471		95
Brightness	ISO 2470C		100
Whiteness Cie	ISO 11475		10-15
Gloss 85°	ISO 2813		1,16 ± 0,05
Mass Density	ISO 534	g/cm <sup>3</sup>	
Shelf Life	20-25°C / 40-60%RH	At least 24 months	
Fire Class		Information upon request	

Alon Tavor Ind. Zone, Israel

[www.jolybar.com](http://www.jolybar.com)

[jolybar@jolybar.com](mailto:jolybar@jolybar.com)

+972-4-6407333