

TECHNICAL DATA SHEET

DDIC050

Product description:

- Clear PET Gloss Self Adhesive 50my
- Applications: Label for advertising products, signage, decoration
- Outdoor and indoor use*
- Adhesive high bond strength to polar and non-polar surfaces
- Optimized for HP-Indigo printing machines
- Excellent ink adhesion
- Excellent machine runnability

Parameter	Value 480 X 330 750 X 530
Dimension (mm)	50 ± 6 Initial tack 10N/25mm (FTM9 glass)
Face Stock Thickness (µm)	Peel at 1800 11N/25mm (FTM1)
Adhesive	200 ± 16 Clear, Gloss
Liner Thickness (µm)	
Surface	

Processing Recommendations:

- Substrates should be acclimatized at room temperature 24 h before printing.
- Print at room temperature with relative humidity between 50-60%.

Storage Conditions:

- Storage should be at temperatures of 10-30oC and relative humidity of 50-60%. Do not expose to direct Sun light.
- Keeping the recommended storage conditions in original packaging will increase product shelf life up to 1 year.

*Users should perform their own tests in order to verify the suitability for a specific application

Alon Tavor Ind. Zone, Israel

www.jolybar.com

jolybar@jolybar.com

+972-4-6407333

1.20