

# TECHNICAL DATA SHEET

## DDIG050

### Product description:

White PET Gloss Self Adhesive 50my

Applications: Label for advertising products, signage, decoration

Outdoor and indoor use\*

Adhesive high bond strength to polar and non-polar surfaces

Optimized for HP-Indigo printing machines

Excellent ink adhesion

Excellent machine runnability

Parameter	Value 480 X 330 750 X 530
Dimension (mm)	50 ± 6 Initial tack 10N/25mm (FTM9 glass)
Face Stock Thickness (µm)	Peel at 1800 11N/25mm (FTM1) 200
Adhesive	± 16 White, Gloss
Liner Thickness (µm)	
Surface	

### Processing Recommendations:

Substrates should be acclimatized at room temperature 24 h before printing.

Print at room temperature with relative humidity between 50-60%.

### Storage Conditions:

- Storage should be at temperatures of 10-30oC and relative humidity of 50-60%. Do not expose to direct Sun light.
- Keeping the recommended storage conditions in original packaging will increase product shelf life up to 1 year.

\*Users should perform their own tests in order to verify the suitability for a specific application

Alon Tavor Ind. Zone, Israel

[www.jolybar.com](http://www.jolybar.com)

[jolybar@jolybar.com](mailto:jolybar@jolybar.com)

+972-4-6407333

1.20